# Safety Data Sheet



# 1. Identification

Date Printed: 7/5/2025

Product Information: M280-0221,M280-0221PLARM,M280-0221PLBR,M280-0221PLMW2A,M280-0221PL

MW9,M280-0221PLWM,M285-3010,M285-3010B,M285-3010BC,MC280-0221

Product Name: ULTRA MARK 53 (M) R

Recommended Use: Surface Preparation or Protection

Supplied by: Mohawk Finishing Products

Division of RPM Industrial Coatings Group

3194 B Hickory Blvd Hudson, NC 28638

USA

 Company Phone No:
 (800) 522-8266

 Emergency Phone No. CHEMTREC:
 (800) 424-9300

International Emergency No. CHEMTREC: (703) 527-3887 (Collect calls are accepted)

### 2. Hazards Identification

#### **GHS Classification**

Eye Dam. 1, Flam. Liq. 2, Skin Irrit. 2, STOT SE 3 NE, STOT SE 3 RTI

### Symbol(s) of Product







Signal Word Danger

### **GHS HAZARD STATEMENTS**

Flammable Liquid, category 2 H225 Highly flammable liquid and vapour.

Skin Irritation, category 2 H315 Causes skin irritation.

STOT, single exposure, category 3, RTI H335 May cause respiratory irritation.

STOT, single exposure, category 3, NE H336 May cause drowsiness or dizziness.

Serious Eye Damage, category 1 H318 Causes serious eye damage.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P235 Store in a well-ventilated place. Keep cool.

#### **GHS SDS PRECAUTIONARY STATEMENTS**

P210 Keep away from heat. - No smoking.

P240 Ground/Bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

Date Printed: 7/5/2025 Product:

M280-0221,M280-0221PLARM,M280-0221PLBR,M280-0221PLMW2A,M280-0221PLMW

9,M280-0221PLWM,M285-3010,M285-3010B,M285-3010BC,MC280-0221

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash face, hands and any exposed skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

P405 Store locked up.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P310 Immediately call a POISON CENTER or doctor/physician.

# 3. Composition/Information on ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
ethanol	64-17-5	30-60	GHS02	H225
butanol	71-36-3	10-30	GHS02-GHS05-	H226-302-315-318-332-335-336
			GHS07	
isopropanol	67-63-0	1-5	GHS02-GHS07	H225-302-319-336
pm acetate	108-65-6	1-5	GHS02-GHS07	H226-332
dipropylene glycol monomethyl ether	34590-94-8	1-5	No Information	No Information
silica	68909-20-6	0.1-1	GHS08	H373
aliphatic petroleum distillates	64742-47-8	0.1-1	GHS07-GHS08	H304-332
ethylbenzene	100-41-4	0.1-1	GHS02-GHS07-	H225-304-332-373
•			GHS08	

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### 4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

FIRST AID - SKIN CONTACT: IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

FIRST AID - INGESTION: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

# 5. Fire-fighting Measures

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool

Product: M280-0221,M280-0221PLARM,M280-0221PLBR,M280-0221PLMW2A,M280-0221PLMW

9,M280-0221PLWM,M285-3010,M285-3010B,M285-3010BC,MC280-0221

fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**FIREFIGHTING EQUIPMENT:** This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipeint fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

### 6. Accidental Release Measures

#### **ENVIRONMENTAL MEASURES:** No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

# 7. Handling and Storage





HANDLING: Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

### 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
ethanol	N.D.	1000 ppm	1000 ppm	N.D.
butanol	20 ppm	N.D.	100 ppm	N.D.
isopropanol	200 ppm	400 ppm	400 ppm	N.D.
pm acetate	N.D.	N.D.	N.D.	N.D.
dipropylene glycol monomethyl ether	50 ppm	N.D.	100 ppm	N.D.
silica	N.D.	N.D.	N.D.	N.D.
aliphatic petroleum distillates	N.D.	N.D.	N.D.	N.D.
ethylbenzene	20 ppm	N.D.	100 ppm	N.D.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

### **Personal Protection**



**RESPIRATORY PROTECTION:** Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.



**SKIN PROTECTION:** Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.

Date Printed: 7/5/2025 Product:

M280-0221,M280-0221PLARM,M280-0221PLBR,M280-0221PLMW2A,M280-0221PLMW 9,M280-0221PLWM,M285-3010,M285-3010B,M285-3010BC,MC280-0221



**EYE PROTECTION:** Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



**OTHER PROTECTIVE EQUIPMENT:** No Information



**HYGIENIC PRACTICES:** It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

# 9. Physical and Chemical Properties

Appearance: Colored Liquid Physical State: Liquid

Odor: Moderately Strong Alcohol Odor Threshold: Not Determined

Density, g/cm3: 0.864 pH: Not Determined

Freeze Point, °F: Not Determined Viscosity: Not Determined Partition Coefficient, n-octanol/

Solubility in Water: Not Determined water: Not Determined

**Decomposition temperature, °F**: Not Determined **Explosive Limits, %**: Not Determined

**Boiling Range, °F:** > 100 °F **Flash Point, °F:** 55.4

Combustibility: Supports Combustion Auto-Ignition Temperature, °F: Not Determined Evaporation Rate: Faster than Diethyl Ether Vapor Pressure, mmHg: Not determined

Vapor Density: Not Determined

N.I. = No Information

# 10. Stability and reactivity

**STABILITY:** Stable under normal conditions.

**CONDITIONS TO AVOID:** Heat, flames and sparks. **INCOMPATIBILITY:** Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

# 11. Toxicological information



**Practical Experiences** 

**EMERGENCY OVERVIEW:** No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information
EFFECT OF OVEREXPOSURE - INGESTION: No Information
EFFECT OF OVEREXPOSURE - INHALATION: No Information

Date Printed: 7/5/2025 Product:

M280-0221,M280-0221PLARM,M280-0221PLBR,M280-0221PLMW2A,M280-0221PLMW 9,M280-0221PLWM,M285-3010,M285-3010B,M285-3010BC,MC280-0221

#### **EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information**

**CARCINOGENICITY:** No Information

PRIMARY ROUTE(S) OF ENTRY:

Eye Contact, Skin Contact, Inhalation

### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
64-17-5	ethanol	7060 mg/kg Rat	15,800 mg/kg	124.7 mg/L Rat
71-36-3	butanol	700 mg/kg Rat	3402 mg/kg Rabbit	8000 mg/l Rat
67-63-0	isopropanol	1870 mg/kg Rat	4059 mg/kg Rabbit	72.6 mg/L Rat
108-65-6	pm acetate	8532 mg/kg Rat	>5000 mg/kg Rabbit	>20 mg/L
34590-94-8	dipropylene glycol monomethyl ether	5230 mg/kg Rat	9500 mg/kg Rabbit	>20 mg/l
64742-47-8	aliphatic petroleum distillates	>5000 mg/kg Rat	>2000 mg/kg Rabbit	>13 mg/L Rat
100-41-4	ethylbenzene	3500 mg/kg Rat	15400 mg/kg Rabbit	17.2 mg/L Rat

#### N.I. = No Information

# 12. Ecological information

**ECOLOGICAL INFORMATION:** Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

# 13. Disposal Information



#### **Product**

**DISPOSAL METHOD:** Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

### 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT: UN1993, FLAMMABLE LIQUIDS, N.O.S., 3, II

IATA: UN1993, FLAMMABLE LIQUIDS, N.O.S., 3, II

IMDG: UN1993, FLAMMABLE LIQUIDS, N.O.S., 3, II

Product: Date Printed: 7/5/2025

> M280-0221.M280-0221PLARM.M280-0221PLBR.M280-0221PLMW2A.M280-0221PLMW 9,M280-0221PLWM,M285-3010,M285-3010B,M285-3010BC,MC280-0221

# 15. Regulatory Information

# U.S. Federal Regulations:

### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard

#### **SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

**Chemical Name** CAS-No. Wt. % butanol 71-36-3 21.15

#### TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

**Chemical Name** CAS-No. 556-67-2 octamethylcyclotetrasiloxane

# U.S. State Regulations:

#### **CALIFORNIA PROPOSITION 65**



MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Ethylbenzene, Cancer, 0.1509% Toluene, Reproductive Harm, 0.005%

### 16. Other Information

6/12/2023 7/27/2024 Supersedes Date: **Revision Date:** 

Reason for revision: Substance and/or Product Properties Changed in Section(s):

01 - Product Information

03 - Composition/Information on Ingredients 08 - Exposure Controls/Personal Protection Substance Hazardous Flag Changed Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health: 2 Flammability: Reactivity: 0 Personal Protection: Х

Volatile Organic Compounds, gr/ltr: 724

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.