

# Safety Data Sheet



## 1. Identification

**Product Information:** M104-4010

**Product Name:** COLORED LACQUER ENAMEL MASK WHITE E1

**Recommended Use:** Surface Preparation or Protection

**Supplied by:** Mohawk Finishing Products  
Division of RPM Industrial Coatings Group  
2220 US Hwy 70 SE Suite 100  
Hickory, NC 28602  
USA

**Company Phone No:** (800) 522-8266

**Emergency Phone No. CHEMTREC:** (800) 424-9300

**International Emergency No. CHEMTREC:** (703) 527-3887 (Collect calls are accepted)

## 2. Hazards Identification

### GHS Classification

Carc. 1B, Comp. Gas, Eye Irrit. 2A, Fl Aer, 1, Muta. 1B, STOT RE 2, STOT SE 3 NE

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

20% of the mixture consists of ingredients of unknown acute toxicity

### GHS HAZARD STATEMENTS

Flammable Aerosol, category 1	H222	Extremely flammable aerosol.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Germ Cell Mutagenicity, category 1B	H340	May cause genetic defects.
Carcinogenicity, category 1B	H350	May cause cancer.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Compressed Gas	H280	Contains gas under pressure; may explode if heated.

### GHS SDS PRECAUTIONARY STATEMENTS

P210	Keep away from heat. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P264	Wash face, hands and any exposed skin thoroughly after handling.
P280	Wear eye protection/ face protection.
P405	Store locked up.

- P305+P351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P201 Obtain special instructions before use.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P312 Call a POISON CENTER or doctor if you feel unwell.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.

### 3. Composition/Information on ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
acetone	67-64-1	10-25	GHS02-GHS07	H225-302-319-332-336
propane	74-98-6	10-25	GHS02-GHS04	H220-280
titanium dioxide	13463-67-7	10-25	GHS08	H351
isobutyl acetate	110-19-0	2.5-10	GHS02-GHS07	H225-332
ethyl acetate	141-78-6	2.5-10	GHS02-GHS07	H225-319-332-336
n-butane	106-97-8	2.5-10	GHS02-GHS04	H220-280
n-butyl acetate	123-86-4	2.5-10	GHS02-GHS07	H226-336
toluene	108-88-3	2.5-10	GHS02-GHS07-GHS08	H225-304-315-332-336-373
ethanol	64-17-5	2.5-10	GHS02	H225
cellulose nitrate, cellulose ester	9004-70-0	2.5-10	GHS01	H201
methyl ethyl ketone	78-93-3	2.5-10	GHS02-GHS07	H225-319-332-336
isopropanol	67-63-0	1.0-2.5	GHS02-GHS07	H225-302-319-336
butanol	71-36-3	1.0-2.5	GHS02-GHS05-GHS07	H226-302-315-318-332-335-336
pm acetate	108-65-6	1.0-2.5	GHS02-GHS07	H226-332
petroleum distillate	64742-49-0	0.1-1.0	GHS08	H304-340-350
butyl cellosolve	111-76-2	0.1-1.0	GHS06-GHS07	H302-315-319-330
ethylbenzene	100-41-4	0.1-1.0	GHS02-GHS07-GHS08	H225-304-332-373

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### 4. First-aid Measures



**FIRST AID - EYE CONTACT:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**FIRST AID - SKIN CONTACT:** IF ON SKIN: Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

**FIRST AID - INGESTION:** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

**FIRST AID - INHALATION:** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

### 5. Fire-fighting Measures

**SPECIAL FIREFIGHTING PROCEDURES:** Evacuate all persons from the fire area to a safe location. Move non-burning material, as

feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**FIREFIGHTING EQUIPMENT:** This is a NFPA/OSHA Category 1 flammable aerosol. Follow NFPA 30B, Chapter 4 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipient fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire

## 6. Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

## 7. Handling and Storage



**HANDLING:** Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

**STORAGE:** Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
acetone	250 ppm	500 ppm	1000 ppm	N.D.
propane	N.D.	N.D.	1000 ppm	N.D.
titanium dioxide	0.2 mg/m <sup>3</sup>	N.D.	15 mg/m <sup>3</sup>	N.D.
isobutyl acetate	50 ppm	150 ppm	150 ppm	N.D.
ethyl acetate	400 ppm	N.D.	400 ppm	N.D.
n-butane	N.D.	1000 ppm	N.D.	N.D.
n-butyl acetate	50 ppm	150 ppm	150 ppm	N.D.
toluene	20 ppm	N.D.	200 ppm	300 ppm
ethanol	N.D.	1000 ppm	1000 ppm	N.D.
cellulose nitrate, cellulose ester	N.D.	N.D.	N.D.	N.D.
methyl ethyl ketone	75 ppm	150 ppm	200 ppm	N.D.
isopropanol	200 ppm	400 ppm	400 ppm	N.D.
butanol	20 ppm	N.D.	100 ppm	N.D.
pm acetate	N.D.	N.D.	N.D.	N.D.
petroleum distillate	100 ppm	N.D.	N.D.	N.D.
butyl cellosolve	20 ppm	N.D.	50 ppm	N.D.
ethylbenzene	20 ppm	N.D.	100 ppm	N.D.

**Further Advice:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

**Personal Protection**

**RESPIRATORY PROTECTION:** Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.



**SKIN PROTECTION:** Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



**EYE PROTECTION:** Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



**OTHER PROTECTIVE EQUIPMENT:** No Information



**HYGIENIC PRACTICES:** It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

**9. Physical and Chemical Properties**

<b>Appearance:</b>	Colored Liquid	<b>Physical State:</b>	Aerosol
<b>Odor:</b>	Strong Solvent	<b>Odor Threshold:</b>	Not Determined
<b>Density, g/cm<sup>3</sup>:</b>	0.848	<b>pH:</b>	Not Determined
<b>Freeze Point, °F:</b>	Not Determined	<b>Viscosity:</b>	Not Determined
<b>Solubility in Water:</b>	Not Determined	<b>Partition Coefficient, n-octanol/ water:</b>	Not Determined
<b>Decomposition temperature, °F:</b>	Not Determined	<b>Explosive Limits, %:</b>	Not Determined
<b>Boiling Range, °F:</b>	Not Determined	<b>Flash Point, °F:</b>	-76 ° F
<b>Combustibility:</b>	Supports Combustion	<b>Auto-Ignition Temperature, °F:</b>	Not Determined
<b>Evaporation Rate:</b>	Faster than Diethyl Ether	<b>Vapor Pressure, mmHg:</b>	Not Determined
<b>Vapor Density:</b>	Not Determined		
<b>N.I. = No Information</b>			

**10. Stability and reactivity**

**STABILITY:** Stable under normal conditions.

**CONDITIONS TO AVOID:** Heat, flames and sparks.

**INCOMPATIBILITY:** Acids, Bases, Oxidizing agents

**HAZARDOUS DECOMPOSITION PRODUCTS:** Not determined.

## 11. Toxicological information



### Practical Experiences

**EMERGENCY OVERVIEW:** No Information

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** No Information

**EFFECT OF OVEREXPOSURE - INGESTION:** No Information

**EFFECT OF OVEREXPOSURE - INHALATION:** No Information

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** No Information

**CARCINOGENICITY:** May cause cancer.

This product contains Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

**PRIMARY ROUTE(S) OF ENTRY:**

Eye Contact, Inhalation

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
67-64-1	acetone	1800 mg/kg Rat	20000 mg/kg Rabbit	50.1 mg/L Rat
74-98-6	propane	N.I.	N.I.	658 mg/L Rat
13463-67-7	titanium dioxide	>10000 mg/kg Rat	>10000 mg/kg Rabbit	>20 mg/l
110-19-0	isobutyl acetate	15400 mg/kg Rat	>17400 mg/kg Rabbit	>20 mg/l
141-78-6	ethyl acetate	5620 mg/kg Rat	>18000 mg/kg Rabbit	200 mg/l Rat
123-86-4	n-butyl acetate	14130 mg/kg Rat	>17600 mg/kg Rabbit	23.4 mg/l Rat
108-88-3	toluene	2600 mg/kg Rat	12000 mg/kg Rabbit	12.5 mg/L Rat
64-17-5	ethanol	7060 mg/kg Rat	15,800 mg/kg	124.7 mg/L Rat
9004-70-0	cellulose nitrate, cellulose ester	>5000 mg/kg Rat	>5000 mg/kg	>20 mg/l
78-93-3	methyl ethyl ketone	2483 mg/kg Rat	5000 mg/kg Rabbit	>20 mg/l
67-63-0	isopropanol	1870 mg/kg Rat	4059 mg/kg Rabbit	72.6 mg/L Rat
71-36-3	butanol	700 mg/kg Rat	3402 mg/kg Rabbit	8000 mg/l Rat
108-65-6	pm acetate	8532 mg/kg Rat	>5000 mg/kg Rabbit	>20 mg/L
64742-49-0	petroleum distillate	>5000 mg/kg Rat	>3160 mg/kg Rabbit	54 mg/l Rat
111-76-2	butyl cellosolve	470 mg/kg Rat	>2000 mg/kg Rabbit	>4.9 mg/l
100-41-4	ethylbenzene	3500 mg/kg Rat	15400 mg/kg Rabbit	17.2 mg/L Rat

N.I. = No Information

## 12. Ecological information

**ECOLOGICAL INFORMATION:** Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

## 13. Disposal Information



Product

**DISPOSAL METHOD:** Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

## 14. Transport Information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

DOT: LIMITED QUANTITY  
 IATA: ID8000, CONSUMER COMMODITY, 9  
 IMDG: LIMITED QUANTITY UN1950

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>
toluene	108-88-3	4.60
butanol	71-36-3	1.62

#### TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
octamethylcyclotetrasiloxane	556-67-2
lead	7439-92-1

**U.S. State Regulations:****CALIFORNIA PROPOSITION 65**

 WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Titanium Dioxide, Cancer, 10.1219%  
Toluene, Reproductive Harm, 4.5962%

**16. Other Information**

**Revision Date:** 7/26/2024 **Supersedes Date:** 12/1/2023

**Reason for revision:** Product Composition Changed  
Substance and/or Product Properties Changed in Section(s):  
01 - Product Information  
03 - Composition/Information on Ingredients  
08 - Exposure Controls/Personal Protection  
09 - Physical & Chemical Information  
15 - Regulatory Information  
16 - Other Information  
Revision Statement(s) Changed

**Datasheet produced by:** Regulatory Department

**HMIS Ratings:**

<b>Health:</b>	2	<b>Flammability:</b>	4	<b>Reactivity:</b>	0	<b>Personal Protection:</b>	X
----------------	---	----------------------	---	--------------------	---	-----------------------------	---

**Volatile Organic Compounds, gr/ltr:** 601

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H201	Explosive; mass explosion hazard.
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapor.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS01



GHS02



GHS04



GHS05



GHS06



GHS07



GHS08



The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.