Safety Data Sheet



1. Identification

Product Information: M734-0057

Product Name: PATCHAL PUTTY PLATINUM GREY KMC #FL055- 4 oz

Recommended Use: Surface Preparation or Protection

Mohawk Finishing Products Supplied by:

Division of RPM Industrial Coatings Group

2220 US Hwy 70 SE Suite 100

Hickory, NC 28602

(800) 424-9300

USA

Company Phone No: (800) 522-8266 **Emergency Phone No. CHEMTREC:**

International Emergency No. CHEMTREC: (703) 527-3887 (Collect calls are accepted)

2. Hazards Identification

GHS Classification

Carc. 1B, Flam. Solid 1, Muta. 1B

Symbol(s) of Product





Signal Word Danger

GHS HAZARD STATEMENTS

H228 Flammable solid. Flammable Solid, category 1

Germ Cell Mutagenicity, category 1B H340 May cause genetic defects.

Carcinogenicity, category 1B H350 May cause cancer.

GHS LABEL PRECAUTIONARY STATEMENTS

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P405 Store locked up.

P201 Obtain special instructions before use.

P308+P313 IF exposed or concerned: Get medical advice/attention.

GHS SDS PRECAUTIONARY STATEMENTS

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/ equipment.

3. Composition/Information on ingredients

| Chemical Name | <u>CAS-No.</u> | <u>Wt. %</u> | GHS Symbols | GHS Statements |
|------------------------------|----------------|--------------|----------------|----------------|
| crystalline silica | 14808-60-7 | 40-55 | No Information | No Information |
| petroleum distillate | 64742-48-9 | 25-40 | GHS08 | H304-340-350 |
| modified complex hydrocarbon | 64742-60-5 | 2.5-10 | GHS07 | H332 |
| mixed glycercides | 68308-54-3 | 2.5-10 | No Information | No Information |
| pariffin wax | 8002-74-2 | 2.5-10 | GHS07 | H332 |
| titanium dioxide | 13463-67-7 | 2.5-10 | GHS08 | H351 |

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN: Gently wash with plenty of Soap and Water. If skin irritation occurs: Get medical advice/ attention.

FIRST AID - INGESTION: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

5. Fire-fighting Measures

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

FIREFIGHTING EQUIPMENT: This is a NFPA/OSHA flammable solid. Follow NFPA 400, Chapters 5 and 13 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipient fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

7. Handling and Storage





HANDLING: Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and

bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

| Chemical Name | ACGIH TLV-TWA | ACGIH-TLV STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|------------------------------|---------------|----------------|--------------|------------------|
| crystalline silica | 0.025 mg/m3 | N.D. | 50 μg/m3 | N.D. |
| petroleum distillate | N.D. | N.D. | N.D. | N.D. |
| modified complex hydrocarbon | N.D. | N.D. | N.D. | N.D. |
| mixed glycercides | N.D. | N.D. | N.D. | N.D. |
| pariffin wax | 2 mg/m3 | N.D. | N.D. | N.D. |
| titanium dioxide | 0.2 mg/m3 | N.D. | 15 mg/m3 | N.D. |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

Personal Protection



RESPIRATORY PROTECTION: In case of insufficient ventilation wear suitable respiratory equipment.



SKIN PROTECTION: Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



EYE PROTECTION: Safety glasses



OTHER PROTECTIVE EQUIPMENT: No Information



HYGIENIC PRACTICES: It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

9. Physical and Chemical Properties

Appearance: Solid Physical State: SOLID

Odor: Oily Hydrocarbon Odor Threshold: Not determined

Density, g/cm3: 1.274 pH: Not determined

Freeze Point, °F: Not determined Viscosity: Not determined

Solubility in Water:

Not determined

Partition Coefficient, n-octanol/
water:

Not determined

Decomposition temperature, °F: Not determined Explosive Limits, %: Not determined

Boiling Range, °F: Not determined Flash Point, °F: 106 ° F

Combustibility: Supports Combustion Auto-Ignition Temperature, °F: Not determined Evaporation Rate: Vapor Pressure, mmHg: Not determined

Vapor Density: Not determined

N.I. = No Information

10. Stability and reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Heat, flames and sparks. **INCOMPATIBILITY:** Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

11. Toxicological information



Practical Experiences

EMERGENCY OVERVIEW: No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information
EFFECT OF OVEREXPOSURE - INGESTION: No Information
EFFECT OF OVEREXPOSURE - INHALATION: No Information
EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

CARCINOGENICITY: May cause cancer.

This product contains Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to

sanding, grinding, cutting, or other surface preparation activities.

PRIMARY ROUTE(S) OF ENTRY:

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
|------------|------------------------------|------------------|---------------------|--------------|
| 14808-60-7 | crystalline silica | >5000 mg/kg | >5000 mg/kg | >20 mg/l Rat |
| 64742-48-9 | petroleum distillate | >5000 mg/kg Rat | >3160 mg/kg Rabbit | >20 mg/L Rat |
| 64742-60-5 | modified complex hydrocarbon | >5000 mg/kg Rat | >3600 mg/kg Rabbit | >20 |
| 68308-54-3 | mixed glycercides | >5001 | >5001 | >20.1 |
| 8002-74-2 | pariffin wax | >3750 mg/kg Rat | >3600 mg/kg Rabbit | >14 mg/l |
| 13463-67-7 | titanium dioxide | >10000 mg/kg Rat | >10000 mg/kg Rabbit | >20 mg/l |

N.I. = No Information

12. Ecological information

ECOLOGICAL INFORMATION: Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

13. Disposal Information



Product

DISPOSAL METHOD: Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT: NOT RESTRICTED

IATA: NOT RESTRICTED

IMDG: NOT RESTRICTED

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Chronic Health Hazard

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical Name CAS-No. 7440-66-6 zinc 7439-92-1 lead

U.S. State Regulations:

CALIFORNIA PROPOSITION 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Crystalline Silica, Cancer, 42.3578% Mercury, Reproductive Harm, 0%

NOTICE

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

16. Other Information

Supersedes Date: 4/1/2023 6/14/2023 **Revision Date:**

Reason for revision: Substance and/or Product Properties Changed in Section(s):

05 - Flammability Information 11 - Toxicological Information Substance Chemical Name Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

| Health: | 2 | Flammability: | 1 | Reactivity: | 0 | Personal Protection: | X |
|---------|---|---------------|---|-------------|---|----------------------|---|
| | | | | | | | |

Volatile Organic Compounds, gr/ltr: 400

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H304 May be fatal if swallowed and enters airways.

H332 Harmful if inhaled.

H340 May cause genetic defects.

H350 May cause cancer.

H351 Suspected of causing cancer.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS07



GHS08



The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.