



# FABRIC GUARD TREATMENT

## TECHNICAL DATA SHEET

### PRODUCT NUMBER

### DESCRIPTION

M103-0202, M103-0202PB FABRIC GUARD TREATMENT

### PRODUCT DESCRIPTION:

Mohawk Fabric Guard® Fabric Treatment is a water based stain protector that can be easily applied to any textile surface, and provides excellent repellency to stains. This new technology protects all water cleanable textiles.

### ADVANTAGES:

1. New 32 oz. trigger spray
2. Water based technology
3. PFAS Free

### PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Water Base
Color	Clear
Sheen	None
Viscosity	21 Second Zhan1
WPG	8.343581941 lbs/gal
Solids by Volume	1.477577649 ±1%
Solids by Weight	1.491769122 ±1%
Flash Point	200.000000000 °F
HMIS	H: 1, F: 0, R: 0, P: X
Coating VOC (g/l)	146.811576865 g/l
Coating VOC (Lb/Gal)	1.225206356 lbs/gal
Material VOC (g/l)	2.664760327 g/l
Material VOC (Lb/Gal)	0.022238582 lbs/gal
#VOC/#Solid	0.178670537 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	23.699988696 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	None
Reducer	None
Retarder	None
AirDry	Cure in 48 hours
Oven Dry	None
Shelf-Life (Unopened)	12 months
Pot-Life (Catalyzed)	None
Recoat Instruction	None
PH	5.7
Contains UV Absorber	

Water - CAS 7732-18-5 - solvent  
Proprietary Resin - CAS Not Available - resin  
Benzophenone 4 - CAS 4065-45-6 UV absorber  
Isopropanol - CAS 67-63-0 solvent

---

**DIRECTIONS:**

Pre-test on material before using. Be sure the textile is clean. Apply solution to textile surface, 6-8 inches away from fabric surface. Allow to air dry for 10 minutes.

*The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.*

*Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.*

*It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.*

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.