



QUICK CLEAN 9738511

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

ACQCLN,M107-3012

QUICK CLEAN 9738511

PRODUCT DESCRIPTION:

Mohawk QUICK CLEAN is a combination of solvents that removes unwanted foreign materials from most surfaces prior to applying a new finish or repair work of finished surfaces. QUICK CLEAN is ideal for cabinets, furniture, appliances, woodwork, and other finished surfaces.

ADVANTAGES:

- Remove unwanted glaze during the glazing process
- Remove labels and glue from most surfaces
- Clean and prepare finished surfaces prior to applying an additional finish coat

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	solvent cleaner
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	5.781764303 lbs/gal
Solids by Volume	0.003225661 ±1%
Solids by Weight	0.005151779 ±1%
Flash Point	-76.000000000 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l)	692.769997504 g/l
Coating VOC (Lb/Gal)	5.781466439 lbs/gal
Material VOC (g/l)	692.769997520 g/l
Material VOC (Lb/Gal)	5.781466439 lbs/gal
#VOC/#Solid	19409.752232126 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	14.648873302
Spread Rate	0.050378641 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

C8-9 Alkane/Cycloalkane - CAS 64742-49-0 - Solvent
Petroleum Gases, Liquefied, Sweetened - CAS 68476-86-8 - propellant
Proprietary Fragrance - CAS not available - fragrance
Benzene - CAS 71-43-2 - not intentionally added.

DIRECTIONS:

Spray QUICK CLEAN on to a clean white absorbent cloth. Test the surface that you will be cleaning in an inconspicuous area by rubbing the area with the wet part of the cloth. If the surface becomes tacky then do not use this product to clean. Briskly wipe over surface with your QUICK CLEAN moistened clean white cloth, constantly revolving the cloth while wiping, so that foreign material will absorb into the cloth rather than be redistributed on the surface. Once the surface has been damp washed in the above manner, wipe off residue with a clean dry cloth and allow to dry for a few minutes before the application of a finish or before polishing. Use only as directed.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.