



CLASSIC CARE™ POLISH

TECHNICAL DATA SHEET

PRODUCT NUMBER

M107-0444

DESCRIPTION

CLASSIC CARE™ POLISH

PRODUCT DESCRIPTION:

Classic Care™ Polish is a high quality product for maintaining beauty of the finish on fine furniture. Classic Care™ Polish will clean smears, smudges and prints while leaving a durable gloss wax protection. Also may be used on appliances, counter tops and stainless steel surfaces.

ADVANTAGES:

1. Cleans smears, smudges & prints
2. Durable gloss wax protection
3. Use on appliances, counter tops and stainless steel

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Water base polish
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	7.693970620 lbs/gal
Solids by Volume	3.144075356 ±1%
Solids by Weight	3.582673510 ±1%
Flash Point	200.000000000 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l)	482.596925658 g/l
Coating VOC (Lb/Gal)	4.027480894 lbs/gal
Material VOC (g/l)	103.957707995 g/l
Material VOC (Lb/Gal)	0.867572213 lbs/gal
#VOC/#Solid	3.147370559 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000179975
Spread Rate	50.430968710 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	12 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	8

Water - CAS 7732-18-5 - solvent
Isobutane - CAS 75-28-5 - propellant
Proprietary Resin - CAS not available - hydrophobe
Butane - CAS 106-97-8 - propellant
Proprietary Rheology Modifier - CAS not available - rheology
Benzoic acid, ammonium salt - CAS 1863-63-4 - anti-corrosive
Ammonium Hydroxide - CAS 1336-21-6 - pH control
Proprietary Fragrance - CAS not available - fragrance
Methylparaben - CAS 99-76-3 - preservative
Formaldehyde - CAS 50-00-0 - not intentionally added

DIRECTIONS:

SHAKE WELL BEFORE USING. For best results, use only when can temperature is between 65° and 90°F. Spray small amount into clean cloth and polish the surface. If product is sprayed directly on to the surfaces, wipe immediately. Do not allow polish to dry on surfaces. Discard empty can in trash pick-up. Do not place in home compactor or burn.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.