



# LEMON OIL POLISH AEROSOL

## TECHNICAL DATA SHEET

### PRODUCT NUMBER

### DESCRIPTION

M107-0466

LEMON OIL POLISH AEROSOL

### PRODUCT DESCRIPTION:

Lemon Oil Polish is used for all types of furniture, paneling, and interior woodwork. Lemon Oil Polish is a longtime favorite among craftsmen and antique restorers because of its citrus smell and ability to revive old worn finishes.

### ADVANTAGES:

1. Easy to use
2. Quick results
3. Pleasant odor

### PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Oil Polish
Color	Clear
Sheen	N/A
Viscosity	N/A
WPG	6.321416447 lbs/gal
Solids by Volume	1.598085803 ±1%
Solids by Weight	2.023864919 ±1%
Flash Point	-76.000000000 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l)	742.139876567 g/l
Coating VOC (Lb/Gal)	6.193479517 lbs/gal
Material VOC (g/l)	742.139876604 g/l
Material VOC (Lb/Gal)	6.193479517 lbs/gal
#VOC/#Solid	48.410412243 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.007615349
Spread Rate	25.633296280 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	Buff dry
Oven Dry	N/A
Shelf-Life (Unopened)	24 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

Hydrotreated Middle Alkanes - CAS 64742-46-7 - luster/sheen  
Petroleum Gases, Liquefied, Sweetened - CAS 68476-86-8 - propellant  
Dearomatized Alkanes - CAS 64742-48-9 - solvent  
Hydrotreated Light Alkanes - CAS 64742-47-8 - solvent  
Proprietary Fragrance - CAS not available - fragrance  
Proprietary Anti-Corrosive - CAS not available - anti-corrosive  
Benzene - CAS 71-43-2 - not intentionally added

---

**DIRECTIONS:**

SHAKE WELL BEFORE USING. Apply Lemon Oil Polish to cloth and apply to surface. Wipe dry with another cloth.

*The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.*

*Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.*

*It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.*

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.