



CRYSTAL & GLASS CLEANER

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M107-0485

CRYSTAL & GLASS CLEANER

PRODUCT DESCRIPTION:

Mohawk® CRYSTAL & GLASS CLEANER loosens dirt in seconds without leaving a dirt-catching film!

ADVANTAGES:

1. Easy to use
2. Dries in seconds
3. Non-dirt catching

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Water base cleaner
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	7.613450266 lbs/gal
Solids by Volume	0.164848709 ±1%
Solids by Weight	0.223107858 ±1%
Flash Point	200.000000000 °F
HMIS	H: 1, F: 4, R: 0, P: X
Coating VOC (g/l)	595.984193899 g/l
Coating VOC (Lb/Gal)	4.973746882 lbs/gal
Material VOC (g/l)	133.740588029 g/l
Material VOC (Lb/Gal)	1.116123279 lbs/gal
#VOC/#Solid	65.707626461 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000014029
Spread Rate	2.644173292 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	9.5

Water - CAS 7732-18-5 - solvent
Isobutane - CAS 75-28-5 - propellant
Isopropanol - CAS 67-63-0 - solvent
Butane - CAS 106-97-8 - propellant
Ammonium Hydroxide - CAS 1336-21-6 - pH adjustment
Benzoic acid, ammonium salt - CAS 1863-63-4 - anti-corrosive
Benzyl-Polyethylene Glycol tert-Octylphenyl Ether - CAS 60864-33-7 - surfactant

DIRECTIONS:

SHAKE WELL BEFORE USING. Hold container upright about 6 inches from glass surface. Depress nozzle to apply the cleaner – use sparingly. Spread foam with a cloth or paper towel and wipe clean immediately with a second clean cloth or paper towel.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.