



8XOZ POLISH AEROSOL

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M107-0860,M107-0860IM,M 8XOZ POLISH AEROSOL
C107-0860,U107-0860

PRODUCT DESCRIPTION:

CLEANS, PROTECTS AND POLISHES all enameled, varnished and lacquered wood or metal surfaces, leather, linoleum, tile, glass, porcelain, masonite. EXCELLENT FOR: Venetian Blinds, Bathroom Fixtures, Windows, Mirrors, Furniture, Pianos, Woodwork, All Kitchen Appliances.

ADVANTAGES:

- Antistatic agent for less dusting, lower VOC
- Ultraviolet light absorber to protect the color of the wood
- Lemon scent for a fresh, clean fragrance
- Extended evaporation rate meaning larger pieces can be polished with greater ease

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Polish
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	7.160224294 lbs/gal
Solids by Volume	18.194159420 ±1%
Solids by Weight	16.736475719 ±1%
Flash Point	200.000000000 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l)	519.774630955 g/l
Coating VOC (Lb/Gal)	4.337744988 lbs/gal
Material VOC (g/l)	315.471083688 g/l
Material VOC (Lb/Gal)	2.632743175 lbs/gal
#VOC/#Solid	2.196938285 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	291.834317097 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	24 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	7
Contains UV Absorber	

Water - CAS 7732-18-5 - solvent
Hydrotreated Light Alkanes - CAS 64742-47-8 - solvent
Petroleum Gases, Liquefied, Sweetened - CAS 68476-86-8 - propellant
Castor oil, oxidized - CAS 68187-84-8 - luster/shine
Hydrotreated Middle Alkanes - CAS 64742-46-7 - solvent
Mineral Oil - CAS 8042-47-5 - luster/shine
Proprietary Solvent - CAS not available - solvent
Secondary Alcohol Ethoxylate - CAS 84133-50-6 - surfactant

Proprietary Fragrance - CAS not available - fragrance
Sodium Hydroxide - CAS 1310-73-2 - pH adjuster
Benzophenone-4 - CAS 4065-45-6 - UV absorber
1-Propanaminium, 3-(dodecyloxy)-2-hydroxy-N,N-bis(2-hydroxyethyl)-N-methyl-, methyl sulfate (salt) - CAS 18602-17-0 - anti-static

DIRECTIONS:

SHAKE WELL. Clean and wipe surfaces well. Spray a small quantity of polish on a clean, soft, lint-free cloth and apply in the conventional manner. For stainless steel and formica, apply with dampened sponge. USE SPARINGLY. OZ® does not require excessive rubbing - the surface brightens immediately and will not show finger marks. Previously waxed and oil polished surfaces can cause smudging because of build up. If so, remove with mild detergent and warm water before applying OZ®. Keep from freezing and do not apply to flat painted surfaces.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.