

## **ULTRA® MARK WW CASHMERE**

PRODUCT NUMBER

**DESCRIPTION** 

M280-0182

ULTRA® MARK WW CASHMERE

PRODUCT DESCRIPTION:

TECHNICAL DATA SHEET

N/A

## PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology         N/A           Color         Red/Brown           Sheen         N/A           Viscosity         N/A           WPG         7.600284890 lbs/gal           Solids by Volume         12.814916335 ±1%           Solids by Weight         20.853908400 ±1%           Flash Point         39.200000000 °F           HMIS         H: 2, F: 3, R: 0, P: X           Coating VOC (g/l)         720.144218904 g/l           Coating VOC (Lb/Gal)         6.009861551 lbs/gal           Material VOC (g/l)         718.450424868 g/l           Material VOC (Lb/Gal)         5.995807337 lbs/gal           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratic (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           AirDry         N/A           AirDry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A           Ph         N/A		
Sheen         N/A           Viscosity         N/A           WPG         7.600284890 lbs/gal           Solids by Volume         12.814916335 ±1%           Solids by Weight         20.853908400 ±1%           Flash Point         39.20000000° F           HMIS         H: 2, F: 3, R: 0, P: X           Coating VOC (g/l)         720.144218904 g/l           Coating VOC (Lb/Gal)         6.009861551 lbs/gal           Material VOC (g/l)         718.450424868 g/l           Material VOC (b/Gal)         5.995807337 lbs/gal           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           AirDry         N/A           AirDry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	Technology	N/A
Viscosity         N/A           WPG         7.600284890 lbs/gal           Solids by Volume         12.814916335 ±1%           Solids by Weight         20.853908400 ±1%           Flash Point         39.200000000 °F           HMIS         H: 2, F: 3, R: 0, P: X           Coating VOC (g/l)         720.144218904 g/l           Coating VOC (Lb/Gal)         6.009861551 lbs/gal           Material VOC (g/l)         718.450424868 g/l           Material VOC (Lb/Gal)         5.995807337 lbs/gal           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           AirDry         N/A           AirDry         N/A           AirDry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoal Instruction         N/A	Color	Red/Brown
WPG         7.600284890 lbs/gal           Solids by Volume         12.814916335 ±1%           Solids by Weight         20.853908400 ±1%           Flash Point         39.200000000 °F           HMIS         H: 2, F: 3, R: 0, P: X           Coating VOC (g/l)         720.144218904 g/l           Coating VOC (Lb/Gal)         6.009861551 lbs/gal           Material VOC (g/l)         718.450424868 g/l           Material VOC (Lb/Gal)         5.995807337 lbs/gal           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           AirDry         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	Sheen	N/A
Solids by Volume 12.814916335 ±1%  Solids by Weight 20.853908400 ±1%  Flash Point 39.200000000 °F  HMIS H: 2, F: 3, R: 0, P: X  Coating VOC (g/l) 720.144218904 g/l  Coating VOC (Lb/Gal) 6.009861551 lbs/gal  Material VOC (g/l) 718.450424868 g/l  Material VOC (Lb/Gal) 5.995807337 lbs/gal  #VOC/#Solid 3.782947690 lbs/lbs solid  VHAP Ratio (#VHAP/#Solid) 1.190016869  Spread Rate 205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)  Catalyst/Ratio N/A  Reducer N/A  Retarder N/A  AirDry N/A  Oven Dry N/A  Shelf-Life (Unopened) 36 months  Pot-Life (Catalyzed) N/A  Recoat Instruction N/A	Viscosity	N/A
Solids by Weight         20.853908400 ± 1%           Flash Point         39.200000000 °F           HMIS         H: 2, F: 3, R: 0, P: X           Coating VOC (g/l)         720.144218904 g/l           Coating VOC (Lb/Gal)         6.009861551 lbs/gal           Material VOC (g/l)         718.450424868 g/l           Material VOC (Lb/Gal)         5.995807337 lbs/gal           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	WPG	7.600284890 lbs/gal
Flash Point         39.20000000 °F           HMIS         H: 2, F: 3, R: 0, P: X           Coating VOC (g/l)         720.144218904 g/l           Coating VOC (Lb/Gal)         6.009861551 lbs/gal           Material VOC (g/l)         718.450424868 g/l           Material VOC (Lb/Gal)         5.995807337 lbs/gal           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           AirDry         N/A           AirDry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	Solids by Volume	12.814916335 ±1%
HMIS         H: 2, F: 3, R: 0, P: X           Coating VOC (g/I)         720.144218904 g/I           Coating VOC (Lb/GaI)         6.009861551 lbs/gaI           Material VOC (g/I)         718.450424868 g/I           Material VOC (Lb/GaI)         5.995807337 lbs/gaI           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	Solids by Weight	20.853908400 ±1%
Coating VOC (g/l)         720.144218904 g/l           Coating VOC (Lb/Gal)         6.009861551 lbs/gal           Material VOC (g/l)         718.450424868 g/l           Material VOC (Lb/Gal)         5.995807337 lbs/gal           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           Retarder         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	Flash Point	39.200000000 °F
Coating VOC (Lb/Gal)         6.009861551 lbs/gal           Material VOC (g/l)         718.450424868 g/l           Material VOC (Lb/Gal)         5.995807337 lbs/gal           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	HMIS	H: 2, F: 3, R: 0, P: X
Material VOC (g/l)         718.450424868 g/l           Material VOC (Lb/Gal)         5.995807337 lbs/gal           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	Coating VOC (g/I)	720.144218904 g/l
Material VOC (Lb/Gal)         5.995807337 lbs/gal           #VOC/#Solid         3.782947690 lbs/lbs solid           VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	Coating VOC (Lb/Gal)	6.009861551 lbs/gal
#VOC/#Solid 3.782947690 lbs/lbs solid  VHAP Ratio (#VHAP/#Solid) 1.190016869  Spread Rate 205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)  Catalyst/Ratio N/A  Reducer N/A  Retarder N/A  AirDry N/A  Oven Dry N/A  Shelf-Life (Unopened) 36 months  Pot-Life (Catalyzed) N/A  Recoat Instruction N/A	Material VOC (g/l)	718.450424868 g/l
VHAP Ratio (#VHAP/#Solid)         1.190016869           Spread Rate         205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)           Catalyst/Ratio         N/A           Reducer         N/A           Retarder         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	Material VOC (Lb/Gal)	5.995807337 lbs/gal
Spread Rate 205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)  Catalyst/Ratio N/A  Reducer N/A  Retarder N/A  AirDry N/A  Oven Dry N/A  Shelf-Life (Unopened) 36 months  Pot-Life (Catalyzed) N/A  Recoat Instruction N/A	#VOC/#Solid	3.782947690 lbs/lbs solid
Catalyst/Ratio         N/A           Reducer         N/A           Retarder         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	VHAP Ratio (#VHAP/#Solid)	1.190016869
Reducer         N/A           Retarder         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	Spread Rate	205.552169278 sq. ft./gal @ 1.0 mil DFT (no loss)
Retarder         N/A           AirDry         N/A           Oven Dry         N/A           Shelf-Life (Unopened)         36 months           Pot-Life (Catalyzed)         N/A           Recoat Instruction         N/A	Catalyst/Ratio	N/A
AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Reducer	N/A
Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Retarder	N/A
Shelf-Life (Unopened) 36 months  Pot-Life (Catalyzed) N/A  Recoat Instruction N/A	AirDry	N/A
Pot-Life (Catalyzed) N/A  Recoat Instruction N/A	Oven Dry	N/A
Recoat Instruction N/A	Shelf-Life (Unopened)	36 months
	Pot-Life (Catalyzed)	N/A
PH N/A	Recoat Instruction	N/A
	PH	N/A

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.