



## WOOL-LUBE

### TECHNICAL DATA SHEET

#### PRODUCT NUMBER

#### DESCRIPTION

M720-1364,M720-1365,M720-1367,M720-1368,M720-1369,M840-5004 WOOL-LUBE

#### PRODUCT DESCRIPTION:

Wool-Lube liquid can be used full strength or slightly reduced with water as a lubricant with steel wool or abrasive pads for smoothing, removing packing marks and scratches from finished surfaces. When reduced with water, Wool-Lube is an excellent sanding lubricant for use with wet/dry sandpapers. Does not interfere with the adhesion or drying of lacquer. Finishes rubbed with Wool-Lube and an abrasive can be recoated immediately after being wiped dry.

#### ADVANTAGES:

1. Easy to use.
2. Will not gum up.
3. Wipes clean.
4. Can be lacquered over.

#### PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Water base lubricant
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	8.512073400 lbs/gal
Solids by Volume	25.000000000 ±1%
Solids by Weight	25.000000000 ±1%
Flash Point	0.000000000 °F
HMIS	H: 1, F: 0, R: 0, P: X
Coating VOC (g/l)	0.000000000 g/l
Coating VOC (Lb/Gal)	0.000000000 lbs/gal
Material VOC (g/l)	0.000000000 g/l
Material VOC (Lb/Gal)	0.000000000 lbs/gal
#VOC/#Solid	0.000000000 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	401.000000000 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	24 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

Water - CAS 7732-18-5 - solvent  
Fatty acids, vegetable-oil, potassium salts - CAS 61788-65-6 - lubricant

---

#### DIRECTIONS:

Place a small amount of Mohawk Wood-Lube on a 3/0 or 4/0 steel wool pad soaked with water, or a second method may be used - reduce liquid Wool-Lube 50/50 with water or to desired level in a container, then simply dip pad into solution. Rub surface in the direction of grain using smooth even strokes to obtain a uniform finish.

For fine satin sheens, wet rub with 400-600 sandpaper and Mohawk Wool-Lube. No polish is necessary after a Wool-Lube rubbing, simply wipe with a clean dry cloth. Wool-Lube is also available in paste form.

*The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.*

*Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.*

*It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.*

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.