



PUMICE STONE 2F 1 LB

TECHNICAL DATA SHEET

PRODUCT NUMBER

M720-1202

DESCRIPTION

PUMICE STONE 2F 1 LB

PRODUCT DESCRIPTION:

Pumice Stone is made from natural lava rock. It can be used as an abrasive and in abrasive compositions. When used to rub down finishes, it can be used dry, water wet or oil wet to furnish lubrication. We recommend the use of Mohawk Rub Cut Oil or Behlen Paraffin Oil with Pumice Stone.

ADVANTAGES:

1. Smooths finish
2. Produces a soft luster

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Abrasive
Color	Natural white
Sheen	N/A
Viscosity	N/A
WPG	20.028408000 lbs/gal
Solids by Volume	100.000000000 ±1%
Solids by Weight	100.000000000 ±1%
Flash Point	999.000000000 °F
HMIS	H: 0, F: 0, R: 0, P: X
Coating VOC (g/l)	0.000000000 g/l
Coating VOC (Lb/Gal)	0.000000000 lbs/gal
Material VOC (g/l)	0.000000000 g/l
Material VOC (Lb/Gal)	0.000000000 lbs/gal
#VOC/#Solid	0.000000000 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

DIRECTIONS:

We recommend the use of Mohawk Rub Cut™ Oil or Behlen Paraffin Oil with Pumice Stone. Apply the oil to the surface and sprinkle proper Pumice Stone grit grade onto the oily surface. Work with the grain of the wood to achieve the best appearance. Pumice Stone is graded according to particle size, 2F being the coarsest, and 4F being extra fine which produces a soft luster.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.