



HYDRO CLEANER WOOD FLOOR CLEANER

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

B730-30006PLDM,M730-300 HYDRO CLEANER WOOD FLOOR CLEANER 06

PRODUCT DESCRIPTION:

Hydro Cleaner is an environmentally friendly waterborne floor cleaner and wax remover for sealed laminate and hardwood floors.

ADVANTAGES:

1. Ready to use
2. Environmentally friendly

PHYSICAL PROPERTIES AND SPECIFICATIONS

| | |
|---------------------------|---|
| Technology | Water base cleaner |
| Color | N/A |
| Sheen | N/A |
| Viscosity | N/A |
| WPG | 8.314803853 lbs/gal |
| Solids by Volume | 0.056799241 ±1% |
| Solids by Weight | 0.075100860 ±1% |
| Flash Point | 200.000000000 °F |
| HMIS | H: 0, F: 0, R: 0, P: X |
| Coating VOC (g/l) | 849.640730065 g/l |
| Coating VOC (Lb/Gal) | 7.090620817 lbs/gal |
| Material VOC (g/l) | 24.802097377 g/l |
| Material VOC (Lb/Gal) | 0.206984272 lbs/gal |
| #VOC/#Solid | 33.146535716 lbs/lbs solid |
| VHAP Ratio (#VHAP/#Solid) | 0.000000000 |
| Spread Rate | 0.911059826 sq. ft./gal @ 1.0 mil DFT (no loss) |
| Catalyst/Ratio | N/A |
| Reducer | N/A |
| Retarder | N/A |
| AirDry | N/A |
| Oven Dry | N/A |
| Shelf-Life (Unopened) | 24 months |
| Pot-Life (Catalyzed) | N/A |
| Recoat Instruction | N/A |
| PH | N/A |

Water - CAS 7732-18-5 - solvent
Dipropylene Glycol Dimethyl Ether - CAS 111109-77-4 - solvent
Isopropanol - CAS 67-63-0 - solvent
Undeceth-40 - CAS 127036-24-2 - surfactant
Benzisothiazolinone - CAS 2634-33-5 - preservative
Proprietary Defoamer - CAS not available - defoamer

DIRECTIONS:

Cleaning Directions: Remove furniture, rugs, etc. Before application, wipe up all food and liquid spills and sweep or vacuum floor. Application directions: For use, spray a light mist over a 6 ft. x 6 ft. (or smaller) square area. Do not pour cleaner directly on the floor. Make light even strokes with a soft cloth or applicator pad to get the desired results. Sponges, string mops or saturated cloths are not recommended. Spray and clean one small area at a time until you have cleaned the entire surface. For best results, rinse with clear water and dry afterwards. Heel marks and heavier dirt marks can be removed with a cloth soaked with Hydro Cleaner. After drying, use Hydro Care to maintain your floors. For best results: Always test in an inconspicuous area prior to use.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.