



FURNITURE WASH GAL

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M712-1757,M830-2002,M830-2004,M830-2005,M830-2007
FURNITURE WASH GAL

PRODUCT DESCRIPTION:

Plush™ Cabinet & Furniture Polish and Restorer may be used on any interior wooden surface to clean and maintain fine cabinetry and furniture pieces without altering the original sheen. Plush™ Cabinet & Furniture Polish and Restorer dries free of oily residue and resists fingerprinting when dry. Plush™ Cabinet & Furniture Polish and Restorer will clean light dirt and fingerprints.

ADVANTAGES:

1. Easy to use.
2. Non-dust collecting.
3. Can be used on all furniture colors.
4. Mild odor.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	N/A
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	7.866687928 lbs/gal
Solids by Volume	1.252543476 ±1%
Solids by Weight	1.172287202 ±1%
Flash Point	106.000000000 °F
HMIS	H: 2, F: 1, R: 0, P: X
Coating VOC (g/l)	784.396780038 g/l
Coating VOC (Lb/Gal)	6.546131725 lbs/gal
Material VOC (g/l)	248.826502135 g/l
Material VOC (Lb/Gal)	2.076565204 lbs/gal
#VOC/#Solid	22.517471879 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.046863418
Spread Rate	20.090797355 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	24 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	9.7

Water - CAS 7732-18-5 - solvent
C9-12 Light Alkanes - CAS 64742-88-7 - solvent
Hydrotreated Light Alkanes - CAS 64742-47-8 - solvent
Propylene Glycol - CAS 57-55-6 - solvent
9-Octadecenamide, N,N-bis(2-hydroxyethyl)-, (Z)- - CAS 93-83-4 - anti-static
Oleic Acid - CAS 112-80-1 - emulsifier
Hydrotreated Heavy Alkanes - CAS 64742-52-5 - defoamer

Aminomethyl Propanol - CAS 124-68-5 - pH, anti-corrosive
Xanthan Gum - CAS 11138-66-2 - rheology
Aluminum, hydroxybis(octadecanoato-O)- - CAS 300-92-5 - defoamer
Benzene - CAS 71-43-2 - not intentionally added

DIRECTIONS:

SHAKE WELL BEFORE USING. Apply Plush™ Cabinet & Furniture Polish and Restorer to the Cleaning and Polishing Cloth making sure that the polish is disbursed in the cloth. Apply polish evenly to entire surface. Always polish the surface of the wood with a slightly damp cloth. Important Note: Never use a dripping wet cloth to polish your finished wood surfaces. Wipe dry with a clean cloth.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.