



LEATHER CLEANER II

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M850-10024	LEATHER CLEANER II

PRODUCT DESCRIPTION:

This mild water-based solution gently and effectively cleans leather surfaces from common household stains. It is pH balanced for leather and formulated for enhanced leather cleaning capabilities. Safe for all top coated and aniline type leathers. Not recommended for use on unfinished leathers like suede or nubuck.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Water Base Cleaner
Color	Clear
Sheen	N/A
Viscosity	N/A
WPG	8.344928941 lbs/gal
Solids by Volume	1.095410590 ±1%
Solids by Weight	1.112492331 ±1%
Flash Point	200.000000000 °F
HMIS	H: 1, F: 0, R: 0, P: X
Coating VOC (g/l)	266.029767823 g/l
Coating VOC (Lb/Gal)	2.220133926 lbs/gal
Material VOC (g/l)	4.042662387 g/l
Material VOC (Lb/Gal)	0.033737773 lbs/gal
#VOC/#Solid	0.363409896 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	17.570385864 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	12 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	6.41

DIRECTIONS:

Always test on an inconspicuous area before use. Gently wipe up stain with a clean cloth or scrape up excess residue from leather surface. Shake bottle well. Next, test the leather for colorfastness by putting cleaner on a clean cloth and rubbing in an inconspicuous area. If significant color transfer occurs, DO NOT USE. If little or no color transfers, proceed with cleaning. Pour Leather Cleaner onto a clean application cloth or sponge, then apply to the leather surface using light circular motions. Do not scrub. Dry gently with a soft, clean cloth and allow approximately 30 minutes for complete drying.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.