



HYDRO CARE WOOD FLOOR PROTECTOR

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M730-30016	HYDRO CARE WOOD FLOOR PROTECTOR

PRODUCT DESCRIPTION:

Hydro Care Protector is an environmentally friendly waterborne wax maintenance product that can be used on all types of wood flooring. Hydro Care Protector is intended to even up (refresh) the appearance of the floor while providing a thin, soil resistant protective coating.

ADVANTAGES:

1. Maintenance product effective on all types of wood flooring
2. Ready to use
3. Environmentally friendly

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Water base
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	8.347206673 lbs/gal
Solids by Volume	0.333651086 ±1%
Solids by Weight	0.351198099 ±1%
Flash Point	200.000000000 °F
HMIS	H: 0, F: 0, R: 0, P: X
Coating VOC (g/l)	248.296012413 g/l
Coating VOC (Lb/Gal)	2.072138039 lbs/gal
Material VOC (g/l)	1.094299202 g/l
Material VOC (Lb/Gal)	0.009132402 lbs/gal
#VOC/#Solid	0.311524140 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	5.351763419 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	24 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	8.4

Water - CAS 7732-18-5 - solvent
Proprietary Surfactant - CAS not available - slip
Proprietary Resin - CAS not available - resin
Benzisothiazolinone - CAS 2634-33-5 - preservative
Undeceth-40 - CAS 127036-24-2 - surfactant
Proprietary Defoamer - CAS not available - defoamer

DIRECTIONS:

Remove furniture, rugs, etc. Wipe up all food and liquid spills and sweep or vacuum floor. Clean floor properly before use with Hydro Cleaner. Gently shake to mix for 30 seconds. Spray a very thin coat of product onto the floor and spread. Work in small sections to keep the applicator pad wet and smooth with the grain. Rinse applicator pad with water. Allow floor to dry at least 1 hour before walking. For best results test on a small inconspicuous area to determine compatibility and to ensure you like the newly polished look. A second coat may be applied after 2 hours if needed. Allow 24 hours before heavy traffic. Apply every 4-8 weeks. Heavier traffic areas may require more frequent applications. Protect from frost and freezing.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.