

PATCHAL PUTTY NOIR

PRODUCT NUMBER

DESCRIPTION

M734-0477

PATCHAL PUTTY NOIR

PRODUCT DESCRIPTION:

TECHNICAL DATA SHEET

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

| Color BLACK Sheen N/A Viscosity N/A WPG 11.173830787 lbs/gal Solids by Volume 50.724536501 ±1% Solids by Weight 70.476468869 ±1% Flash Point 106.000000000 °F HMIS H: 2, F: 1, R: 0, P: X Coating VOC (g/l) 395.295119066 g/l Coating VOC (lb/Gal) 3.298909411 lbs/gal Material VOC (g/l) 395.295119082 g/l Material VOC (lb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.00000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Technology | N/A |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|---------------------------------------------------|
| Viscosity N/A WPG 11.173830787 lbs/gal Solids by Volume 50.724536501 ± 1% Solids by Weight 70.47646869 ± 1% Flash Point 106.00000000 °F HMIS H: 2, F: 1, R: 0, P: X Coating VOC (g/l) 395.295119066 g/l Coating VOC (Lb/Gal) 3.298909411 lbs/gal Material VOC (g/l) 395.295119082 g/l Material VOC (tb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.00000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Color | BLACK |
| WPG 11.173830787 lbs/gal Solids by Volume 50.724536501 ± 1% Solids by Weight 70.476468869 ± 1% Flash Point 106.000000000° F HMIS H: 2, F: 1, R: 0, P: X Coating VOC (g/l) 395.295119066 g/l Coating VOC (Lb/Gal) 3.298909411 lbs/gal Material VOC (g/l) 395.295119082 g/l Material VOC (Lb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.00000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Sheen | N/A |
| Solids by Volume 50.724536501 ±1% Solids by Weight 70.476468869 ±1% Flash Point 106.00000000 °F HMIS H: 2, F: 1, R: 0, P: X Coating VOC (g/l) 395.295119066 g/l Coating VOC (Lb/Gal) 3.298909411 lbs/gal Material VOC (g/l) 395.295119082 g/l Material VOC (Lb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.00000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Viscosity | N/A |
| Solids by Weight 70.476468869 ±1% Flash Point 106.000000000 °F HMIS H: 2, F: 1, R: 0, P: X Coating VOC (g/l) 395.295119066 g/l Coating VOC (Lb/Gal) 3.298909411 lbs/gal Material VOC (g/l) 395.295119082 g/l Material VOC (Lb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | WPG | 11.173830787 lbs/gal |
| Flash Point 106.000000000 °F HMIS H: 2, F: 1, R: 0, P: X Coating VOC (g/l) 395.295119066 g/l Coating VOC (Lb/Gal) 3.298909411 lbs/gal Material VOC (g/l) 395.295119082 g/l Material VOC (Lb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Solids by Volume | 50.724536501 ±1% |
| HMIS H: 2, F: 1, R: 0, P: X Coating VOC (g/l) 395.295119066 g/l Coating VOC (Lb/Gal) 3.298909411 lbs/gal Material VOC (g/l) 395.295119082 g/l Material VOC (Lb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.00000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Solids by Weight | 70.476468869 ±1% |
| Coating VOC (g/l) 395.295119066 g/l Coating VOC (Lb/Gal) 3.298909411 lbs/gal Material VOC (g/l) 395.295119082 g/l Material VOC (Lb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.00000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Flash Point | 106.000000000 °F |
| Coating VOC (Lb/Gal) 3.298909411 lbs/gal Material VOC (g/l) 395.295119082 g/l Material VOC (Lb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | HMIS | H: 2, F: 1, R: 0, P: X |
| Material VOC (g/l) 395.295119082 g/l Material VOC (Lb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.00000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Coating VOC (g/I) | 395.295119066 g/l |
| Material VOC (Lb/Gal) 3.298909411 lbs/gal #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Coating VOC (Lb/Gal) | 3.298909411 lbs/gal |
| #VOC/#Solid 0.418913314 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Material VOC (g/l) | 395.295119082 g/l |
| VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Material VOC (Lb/Gal) | 3.298909411 lbs/gal |
| Spread Rate 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | #VOC/#Solid | 0.418913314 lbs/lbs solid |
| Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | VHAP Ratio (#VHAP/#Solid) | 0.00000000 |
| Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Spread Rate | 813.621565476 sq. ft./gal @ 1.0 mil DFT (no loss) |
| RetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)12 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A | Catalyst/Ratio | N/A |
| AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Reducer | N/A |
| Oven Dry N/A Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Retarder | N/A |
| Shelf-Life (Unopened) 12 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A | AirDry | N/A |
| Pot-Life (Catalyzed) N/A Recoat Instruction N/A | Oven Dry | N/A |
| Recoat Instruction N/A | Shelf-Life (Unopened) | 12 months |
| | Pot-Life (Catalyzed) | N/A |
| PH N/A | Recoat Instruction | N/A |
| | PH | N/A |

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.