



INK REMOVER MARKER

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M874-0001	INK REMOVER MARKER

PRODUCT DESCRIPTION:

Ink Remover removes ball point pen ink from vinyl upholstery, polyester, cotton and wool fabrics. Will not hurt materials. Just dab on and blot off with clean cloth when ink is dissolved. If finish is removed, use Mohawk's Clear Vinyl Spray Finish.

ADVANTAGES:

1. Easy to use.
2. Quick results.
3. Will not ruin fabrics.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Solvent base
Color	Clear
Sheen	N/A
Viscosity	N/A
WPG	7.624861468 lbs/gal
Solids by Volume	0.000000000 ±1%
Solids by Weight	0.000000000 ±1%
Flash Point	51.800000000 °F
HMIS	H: 1, F: 3, R: 0, P: X
Coating VOC (g/l)	913.656650317 g/l
Coating VOC (Lb/Gal)	7.624861468 lbs/gal
Material VOC (g/l)	913.656650265 g/l
Material VOC (Lb/Gal)	7.624861468 lbs/gal
#VOC/#Solid	0.000000000 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	0.000000000 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

Pre-Test on fabrics before use
Methoxyisopropanol - CAS 107-98-2 - solvent
Methanol - CAS 67-56-1 - solvent
Ethoxydiglycol - CAS 111-90-0 - solvent
Ethylene Glycol - 107-21-1 - solvent

DIRECTIONS:

To start the ink to flow, press the pen, nib down, until the nib is wet. Dab the remover in the direction of the ink stain. As the ink dissolves, blot excess with a clean cloth or tissue. Repair the sheen, if necessary with Mohawk's "Vinyl Finish Aerosol".

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.