

Mohawk

Finishing Products, Inc.

Product Data Sheet

FINISHER'S CHOICE CLEARS

M102-0540 (GLOSS), 0541 (SATIN), 0542 (FLAT), 0543 (SEALER)

AVAILABLE IN 13 OZ. AEROSOL

Product Description: Mohawk's highest solids aerosol product line. We offer a choice of three different sheens for the topcoat and a sanding sealer to compliment the hi-solids quality of the topcoats. This product is very suitable for small refinishing and restoration projects.

Advantages:

1. HAP's compliant.
2. Aerosol form – no extra equipment needed.
3. Fast build.
4. Very good flow.
5. Excellent blush resistance.

Product Limitations:

1. For interior use only.

Characteristics:

Weight per gallon: 7.60 ± 0.1 lbs./gal.

Flashpoint: < 0 F/ -17.8 c

Package Viscosity: 31-33 seconds (Sealer), 24-26 seconds (Topcoat) #1 Zahn cup

Dry time: Air Dry @ 72 F, 35% relative humidity

To touch: 5 minutes

To handle: 15 minutes

To sand: 30 minutes

To recoat: 30+ minutes

To package: Overnight

Volatile Organic Compounds (VOC):

Does not exceed 95% VOC

60° Gloss Meter Readings:

Gloss 85+

Satin 45-50

Flat 15-20

Spec. Gravity: $.913 \pm 0.01$

Boiling Range: -30 F/ -34 c

Non Volatile (wt): $16.7 \pm 0.3\%$ (Sealer), 18.3 – 19.8% for Topcoat

Package Life: 3 years

Hazardous Air Pollutants: 0.75 ± 0.05 lb./1 lb. solids

Air Quality Data: Non-Photochemically Reactive

HMIS:

Health: 1

Flammability: 4

Reactivity: 0

Personal Protection: B

Specifications:

Directions: SHAKE WELL BEFORE USING. Surface should be clean, dry, finish sanded with a wood moisture content of 6-8% maximum. For best results, use only when can temperature is between 65 °F and 90°F. Use steady even strokes while spraying. Several thin coats give a better finish than one heavy coat.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

P O Box 22000

Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545