

# Mohawk Finishing Products

A Division of RPM Wood Finishes Group, Inc.

## Product Data Sheet

### Top Coat Matte

M850-20344 - 8 fl. oz. bottle

M850-20347 - 5 liter bottle (1.3 gallons)

-----

**Product Description:** Top Coat Matt is a ready to use, low sheen waterborne topcoat that is tough and scratch resistant. It displays excellent feel, rub resistance and adhesion – all without graying. A mixture of gloss and Matte will produce various degrees of sheen.

-----

### **Characteristics:**

Physical state: Liquid

Package life: Maximum 1 year from date of manufacture, must be kept in original container.

Storage: Protect from freezing. Store above 40° F.

### HMIS:

Health: 2

Flammability: 1

Reactivity: 0

Personal Protection: B

### **Specifications:**

**Leather type usage:** Use Top Coat for the restoration of pigmented leathers.

**Pre-test:** Spray the Top Coat mixture on a hidden area to be sure the opacity and feel of the coating is correct. If not, adjust the mixture.

**Directions:** Mix Gloss and Matte in any ratio to achieve the desired opacity. Add FM Feel Modifiers according to taste. Add Crosslinker 86 in an amount equal to 10 % of the Top Coat to be catalyzed. The catalyst must be added slowly while stirring the Top Coat, and the stirring continued for at least 1 minute after the addition is complete. The above mixture should be spray applied within two hours of the addition of Crosslinker 86.

Spray one coat for a natural feel, two coats to add more rub resistance to the leather. The second coat should be sprayed immediately after the first coat is dry. Dry naturally or with heat. Allow to dry for 24 hours before using the leather.

**Routine care:** Leather Products should be used after the new finish is dry and Leather Cleaner and Leather Protector should be used on a regular basis to keep the leather looking fresh and new.

**Safety cautions:** Use only in a well ventilated area. Avoid contact with eyes, skin and clothing. Avoid breathing vapor. Additional local exhaust ventilation is recommended where mists or vapors may be released.

**KEEP OUT OF REACH OF CHILDREN.**

**MSDS:** If Material Safety Data Sheet is required, contact:  
Mohawk Finishing Products  
Division of RPM Wood Finishes Group, Inc.  
P O Box 22000  
Hickory, NC 28603

Phone: 1-800-545-0047  
Fax: 1-800-721-1545